

Sustainability that supports your business

iR5065Ne

you can

HIGH-VOLUME BLACK AND WHITE MFP

PRINT, COPY, SCAN AND SEND

65 PPM, 4150 SHEETS CAPACITY

MANUFACTURED SUSTAINABLY

PROVEN CANON QUALITY

Enjoy high-volume productivity and added sustainability with Canon's Factory Produced New Models. Created through a rigorous factory process, the iR5065Ne is a new edition of our popular office black and white model.



A sustainable choice

- Sustainable and rigorous factory process which promotes efficient use of available resources
- Strict quality assurance procedures applied
- Reduced dependency on new raw materials by reuse of up to 93% of parts and components by weight
- 91.6% less CO₂ generated during iR5065Ne manufacturing compared to the original models*
- Made in Germany with utmost precision
- All latest firmware and service updates included

Black and white efficiency

- Black and white print, copy, scan, and send functionality in one
- Suitable for the busiest offices and workgroups
- High-volume productivity with 65 ppm per minute
- Paper supply of 4150 sheets for uninterrupted printing
- Intuitive operation from a large colour touch screen
- Secure print, Mailbox and standard hard disk erase protect documents and important information
- Control physical access and set volume quotas per user or department with Department ID
- Integration with a wide number of capture and output management solutions such as uniFLOW and eCopy



Canon

Specifications: iR5065Ne

| OVERVIEW | |
|---------------------------------------|---|
| Machine Type Available Core Functions | Black and White Laser Multifunctional Print, Copy, Scan, Send |
| PRINTER SPECIFICATIONS | |
| Print Speed (BW/CL) | A4: 65 ppm A3: 32 ppm A4R: 47 ppm A5R: 35 ppm |
| Printing Method | Laser Beam Printing |
| Print Resolution | 600 dpi x 600 dpi, 1,200 dpi x 600 dpi (enhanced) |
| Double Sided Printing | Automatic (Standard) |
| Printing From Memory Media | N/A |
| Printing from mobiles/tablets | Canon Mobile Printing: support for printing from iPad/iPhone (iOS) and Android devices. Please, contact your Canon representative for further information. |
| Paper Input (Standard) | Paper cassettes: 2 x 1,500 sheets and 2 x 550 sheets (80 gsm), Multi-purpose tray: 50 sheets |
| Max. input capacity | 4,150 sheets (A4, 80 gsm) |
| Output capacity | 4,000 sheets (A4, 80 gsm) (with optional finisher) |
| Finishing Capabilities | (with optional finisher) Collate, Group, Staple (Corner, Double) |
| Supported Media Types | Cassettes 1 and 2: Plain, Recycled, Heavy (91-200 gsm), Colour, Pre-punched, Letterhead Cassettes 3 and 4: Plain, Recycled, Heavy (91-200 gsm), Colour, Pre-punched, Letterhead, Tab Paper Multi-purpose tray: Plain, Recycled, Heavy (91-200 gsm), Colour, Pre-punched, Letterhead, Transparency, Labels |
| Supported Media Sizes | Cassettes 1 and 2: A4 Cassettes 3 and 4: A4, A4R, A3, A5R Multi-purpose tray: A4, A4R, A3, A5R, Free size: 99 mm x 148 mm to 297 mm x 432 mm |
| Supported Media Weights | Paper cassette 1-4: 64 to 200 gsm Multi-purpose tray: 64 to 200 gsm Duplex: 64 to 200 gsm |
| Page Description Language(s) | UFRII/PCL5/6 (Standard) PostScript Level 3 Emulation (Optional) |
| Fonts | PCL fonts: 80 Roman, 1 Bitmap, PS fonts: 136 Roman fonts |
| Operating System Compatibility | UFRII: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8, MAC OS X (10.5.x or later) PCL: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8 PS: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8, MAC OS X (10.5.x or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows XP/Server 2000/Windows 7/Windows 8 Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. |
| COPY SPECIFICATIONS | |
| Copy Speed | A4: 65 ppm A3: 32 ppm A4R: 47 ppm A5R: 35 ppm |
| First Copy Output Time (FCOT) | Approx. 3.3 sec or less |
| Copy Resolution | Reading: 600 dpi x 600 dpi Copying: 1,200 dpi x 600 dpi (enhanced) |
| Multiple Copy Reduction / Enlargement | Up to 9,999 copies Zoom: 25-400 % in 1 % increments Fixed Zoom Ratio: 25 %, 50 %, 70 %, 100 %, 141 %, 200 %, 400 % |

| SCAN SPECIFICATIONS | |
|--------------------------------------|--|
| Optional/Standard | A standard IMAGE READER UNIT provides: Flatbed scan unit and a 100-sheet duplex automatic document feeder (1 pass duplex scan). |
| Supported Media Sizes | A3, A4, A4R, A5, A5R; Free sizes (W x L): Min. 128 mm x 139.7 mm, Max. 304.8 mm x 432 mm |
| Supported Media Weights | Single-sided scanning: 42 to 128 gsm Double-sided scanning: 50 to 128 gsm |
| Scan Resolution | 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi |
| Double-sided Scanning | 2-sided to 2-sided (Automatic) |
| Scan Speed | Single-sided: 77 ipm (BW, 600 dpi); 77 ipm (BW, 300 dpi) Double-sided: 87 ipm (BW, 600 dpi); 100 ipm (BW, 300 dpi) |
| Scan Methods | Push Scan: Send functionality standard, Pull Scan: TWAIN/WIA Pull scanning, Scan to USB Memory Key: not supported |
| Pull Scan Specifications | TWAIN via Network TWAIN Driver (Colour Network ScanGear); Supported OS: Windows 2000/Windows XP/Windows Server 2003/Windows Vista/Windows Server 2008/Windows 7/Windows 8 (32 bit, 64 bit in compatibility mode)* WIA via Network WIA Driver; Supported OS: Windows Vista/Windows Server 2008/Windows 7/Windows 8 (32 bit, 64 bit)* *The drivers are available via http://software.canon-europe.com/ . |
| SEND SPECIFICATIONS | |
| Optional/Standard | Standard |
| Send Resolution | 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi |
| Destinations | E-Mail/Internet FAX (SMTP), PC (SMB, FTP), WebDAV |
| Address Book/Speed | LDAP (1,000)/Local (Max. 1,800) |
| File Formats | TIFF, PDF |
| Optional Universal Send Feature Sets | UNIVERSAL SEND SEARCHABLE PDF KIT-A1: Enables searchable PDF (OCR). UNIVERSAL SEND PDF SECURITY FEATURE SET-A1: Adds encrypted PDF and device signature PDF. DIGITAL USER SIGNATURE PDF KIT-A1: Enables attaching user electronic signature on PDF. |
| FAX SPECIFICATIONS | |
| Optional/Standard | N/A |
| GENERAL SPECIFICATIONS | |
| Warm-up Time | Approx. 34 sec from power ON |
| Recovery From Sleep Mode | Approx. 30 sec |
| Interface Type | USB 2.0 Hi-Speed; Ethernet: 100Base-TX/10Base-T |
| Network Protocols | TCP/IP (LPD/Port9100/IPP/IPPS/SMB/FTP), IPv6, IPX/SPX (NDS, Bindery), AppleTalk *IPv4/IPv6 support |
| Processor Speed | 533MHz/400MHz (Uses Main unit CPU) |
| Memory | 1 GB |
| Hard Disk Drive | 40 GB |
| Control Panel | 19 cm (7.5 inch) VGA Colour LCD Touch Panel |
| Dimensions (W x D x H) | 643 mm x 743 mm x 1,207 mm |
| Installation Space (W x D) | 1,448 mm x 1,278 mm (without finisher, when multi-purpose tray is extended + cassette drawers open); 2,591 mm x 1,278 mm (with finisher, when multi-purpose tray is extended + cassette drawers open) |
| Weight | Approx. 220 kg |
| Operating Environment | Temperature: 15 to 27.5°C (59 to 81.5 °F) Humidity: 25 to 75 % RH (no condensation) |
| Power Source | AC 220-240 V (±10 %), 50/60 Hz (±2 Hz) |

| Power Consumption | Maximum: Approx. 2.3 KW Standby: Approx. 271 W Sleep mode: Approx. 1.45 W or less ¹ Typical Electricity Consumption (TEC) rating ² : 10.413 kWh |
|--|--|
| Noise Levels | Sound Pressure ³ Active: 67.5 dB Standby: 46.7 dB |
| Software And Printer Management | iW Management Console for centralised management of the device (Consumables and error monitoring and alerts). Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management and remote diagnostics). Canon Driver Configuration Tool; Remote User Interface (RUI); Network ScanGear; MEAP (Multifunctional Embedded Application Platform) |
| Security Features | Standard: IP/Mac Address Filtering, SSL, Secure Print, Data Erase, SSOH, Department ID, Mailbox Optional: Hard disk encryption, secure watermark, device and user signatures, encrypted PDF |
| CONSUMABLES | |
| Toner Cartridge/s | C-EXV 22 TONER BK (yield 48,000 pages*) |
| SPECIFICATIONS FOR OPTIONS | |
| Staple/Booklet Finisher 1 | FINISHER-AD1 ER (External staple finisher): Optional Number of Trays: 3 Upper Tray Capacity: 250 sheets (A4/A5R), 125 sheets (A3/A4R) (80 gsm) Middle Tray Capacity: 1,300 sheets (A4/A5R), 650 sheets (A3/A4R) (80 gsm) Lower Tray Capacity: 2,450 sheets (A4), 1,700 sheets (A5R), 650 sheets (A3/A4R) (80 gsm) Paper Weight: 64 to 200 gsm Staple Position: Corner, double Staple Capacity: A4: 50 sheets; A3/A4R: 30 sheets |
| ADDITIONAL OPTIONS | |
| Print Controller Accessories | PS PRINTER KIT-R1: Enables PostScript printing. BARCODE PRINTER KIT-D1: Enables barcode printing via jet caps technology. |
| Document Publishing | iW DESKTOP: Powerful print publishing software which easily combines documents from different sources, applies finishing to create professional looking documents and seamlessly links to the printer. Includes PDF creation, annotation and compression capabilities for digital workflows such as proofing and authorization. |
| System Accessories | WEB ACCESS SOFTWARE-H1: Provides access to websites and other web-based online content. |
| Device Security Accessories | HDD DATA ENCRYPTION KIT-B2: Encrypts all image data and device settings before storing them on the hard drive of the device. |
| Document Security Accessories | SECURE WATERMARK-B1: Deters duplication of sensitive documents by embedding hidden watermarks that become visible when copied. ENCRYPTED PRINTING SOFTWARE-D1: Encrypts the print job in transit to the device and requires a password at the printer before sensitive documents can be printed. |
| Accessibility Accessories | REMOTE OPERATORS SOFTWARE KIT-B1: Allows use of the device control panel screens from remote computers. |
| Other Options | Staple CRG-J1 GP |
| Standard disclaimers All specifications subject to change without notice Footnotes [1] The quoted sleep mode consumption may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information. [2] Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (http://www.eu-energystar.org). [3] Declared noise emission in accordance with ISO 7779 [4] Based on 6% coverage | |

Software and solutions



Certifications and compatibility



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English
© Canon Europa N.V., 2013

Canon (UK) Ltd

Woodhatch
Reigate
Surrey RH2 8BF
Telephone no 01737 220000
Facsimile 01737 220022
canon.co.uk

Canon Ireland

3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

