



Lexmark M1342

Productivity. Reliability. Security.











Lexmark M1342

Light, compact, and fast, the M1342 supports output up to 40 pages per minute* plus wireless connectivity. The replacement Unison™ toner cartridge offers up to 18,000 pages of output**, while an optional 550-sheet tray supports longer print runs. A 1-GHz multi-core processor powers through big jobs, and Lexmark full-spectrum security helps protect sensitive information.

Speedy, compact printing

- Get monochrome output at up to 40 pages per minute*, with a first page as fast as 5.9 seconds.
- Tackle your printing workload with the power of a 1-GHz dual-core processor and 256 MB of memory.
- Compact dimensions of 222 mm high x 368 mm wide x 363 mm deep helps it fit almost anywhere.

Connect and control

- Connect via Ethernet, USB and Wi-Fi.
- Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- Two-line display lets you configure, interact with, and monitor vital system information.

Sustained output, enduring quality

- Replacement Unison™ toner provides up to 18,000 pages** of output for more printing and less downtime.
- Optional paper tray increases total input capacity to 900 sheets to support longer print runs and enhanced media flexibility.

Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device, over the network, and everywhere in between.
- A range of embedded features harden the device against attacks.
- Standard Confidential Print feature helps ensure output security via simple PIN.

Save paper, save energy

- Automatic two-sided printing is standard.
- Built-in energy-saving modes help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} Average yield based on approximately 5% print coverage.

Lexmark M1342



P/N Hardware 29S0422 Lexmark M1342

P/N **Supplies**

24B7005 Lexmark M/XM1342 18K Toner

Cartridge Lexmark MS/MX331, 431, B3340, B/MB3442, M/XM1342 40K 55B0ZA0

Imaging Unit

P/N **Paper Handling** 29S0600 550-Sheet Tray

P/N Connectivity 1021294 USB Cable - 2 Metre Surge Protective Device, 220-240V SPD0002

P/N **Furniture** 35\$8502 Adjustable Stand

1 Printer with 2-line display 222 x 368 x 363 mm

- 100-Sheet multipurpose feeder 2 Dimensions included as part of base model
- 3 250-Sheet tray Dimensions included as part of base model

550-Sheet Tray 107 x 370 x 378 mm Standard Optional

Product Specifications	Lexmark M1342
Printing	
Display	2-line All Points Addressable (APA) monochrome LCD display
Print Speed	Up to: Black: 40 ppm ¹ (A4)
Time to First Page	As fast as: Black: 5.9 seconds
Print Resolution	Black: 2400 IQ (2400 x 600 dpi), 600 x 600 dpi
Memory	standard: 256 MB / maximum: 256 MB
Hard Disk	Not Available
Recommended Monthly Page Volume	800 - 8,000 Pages ²
Maximum Monthly Duty Cycle	Up to: 80,000 pages per month ³
Supplies ⁴	
Laser Cartridge Yields	up to: 18,000 ⁵ -page High Yield Cartridge
Imaging Unit Estimated Yield	Up to: 40,000 pages, based on 3 average letter/A4-size pages per print job and \sim 5% coverage 6
Cartridge(s) Shipping with Product	3,000 ⁵ -page Return Programme Toner Cartridge
Paper Handling	
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 150-Sheet Output Bin, 250-Sheet Input
Optional Paper Handling	550-Sheet Tray
Paper Input Capacity	Up to: Standard: 350 pages 75 gsm bond / Maximum: 900 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond
Media Types Supported	Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Speciality Media Guide
Media Sizes Supported	Aó, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁷	
Standard Ports	USB Compatible with USB 2.0 Specification (Type B), Fast Ethernet
Noise Level	Operating: 53 dBA (Print)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2,896 Metres (9,500 Feet)
Product Guarantee	1-year Onsite Service + 3-years Parts Only guarantee (Maintenance Kit included)
Size / Weight	H x W x D: 222 x 368 x 363 mm / 9.3 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.47 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

© 2021 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{2 &}quot;Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. 3 "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. 4 Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. 5 Average yield based on approximately 5% print coverage. 6 Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. 7 Printers are sold subject to certain licence/agreement conditions. See www.lexmark.com/printerlicense for details.